

DATE OF PREP: 1/27/88

IPL # 20014

SECTION I

MANUFACTURERS NAME:
SIKKENS AEROSPACE FINISHES
DIVISION OF AKZO COATINGS AMERICA INC.
STREET ADDRESS:
20846 S. NORMANDIE AVE
TORRANCE, CA 90502

EMERGENCY TELEPHONE NO.:
(213) 320-6800

MANUFACTURERS CODE IDENTIFICATION:
683030002

TRADE NAME:
POLYURETHANE CONCENTRATE -

Use with Catalyst X 310A

SECTION II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS:	C.A.S. NO.	* PCT *	* TLV *	* PEL *	* VAPOR *			
			PPM	MG/M3	PPM	MG/M3	PRESS	
2-ETHOXYETHYL ACETATE	111-15-9	*55-70*	SKIN	5.00	27.00*	---	---	2.0
CELLOSOLVE ACETATE		* *	*	---	---	---	---	*
PROPYLENE GLYCOL METHYL ETHER ACETATE	108-65-6	* <5*	*	---	---	---	---	3.8
PM ACETATE		* *	*	---	---	---	---	*

SECTION III - PHYSICAL DATA

BOILING RANGE:
294 - 313 DEG. F

VAPOR DENSITY VS. AIR:
HEAVIER THAN AIR

EVAPORATION RATE VS. ETHER:
SLOWER

PERCENT VOLATILE BY VOLUME:
65.7

WEIGHT PER GALLON:
8.79 LBS.

MATERIAL SAFETY DATA SHEET

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

CATEGORY:

FLASH POINT:

LEL: 1.5

PAINT,
FLAMMABLE LIQUID, UN-1263

40F TCC

OSHA CLASSIFICATION:

FLAMMABLE LIQUID - CLASS IB

EXTINGUISHING MEDIA:

FOAM, CARBON DIOXIDE, DRY CHEMICALS

UNUSUAL FIRE AND EXPLOSION HAZARDS:

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS,
AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.
APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

SPECIAL FIRE FIGHTING PROCEDURES:

WATER MAY BE INEFFECTIVE. WATER SHOULD BE USED TO COOL CONTAINERS EXPOSED TO
FIRE. FIRE FIGHTING PERSONNEL SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

SECTION V - REACTIVITY DATA

STABILITY:

STABLE

INCOMPATIBILITY (MATERIALS TO AVOID):

ONE REASONABLY FORESEEABLE.

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON MONOXIDE, CARBON DIOXIDE, SMOKE, OXIDES OF NITROGEN.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

CONDITIONS TO AVOID:

NOT APPLICABLE

SECTION VI - HEALTH HAZARD DATA

RESHOLD LIMIT VALUE: SEE SECTION II.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NECESSARY.

SKIN CONTACT: WASH WITH SOAP & WATER.

EYE CONTACT: FLUSH WITH WATER FOR AT LEAST 15 MINUTES, CONSULT A PHYSICIAN.

INGESTION: DRINK ONE OR TWO GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING.

CONSULT PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY.

MEDICAL CONDITIONS PRONE TO AGGRAVATION: NONE EXPECTED

THE FOLLOWING HAZARDS HAVE BEEN REPORTED TO BE ASSOCIATED WITH THE INDIVIDUAL COMPONENTS OF THIS PRODUCT. THESE HAZARDS MAY NOT ALL BE ASSOCIATED WITH THE FINISHED PRODUCT.

ACUTE:

EYE IRRITANT, CONTACT MAY CAUSE EYE BURNS OR CORNEAL INJURY.

VAPORS MAY BE IRRITATING AND CAUSE COUGHING, HEADACHE, NAUSEA, AND VOMITING.

PROLONGED CONTACT WITH THE SKIN MAY LEAD TO EXTRACTION OF NATURAL OILS WITH RESULTANT MILD IRRITATION.

CAN BE ABSORBED THROUGH THE SKIN.

IF SWALLOWED MAY CAUSE HEADACHE, NAUSEA, VOMITING, DIZZINESS, WEAKNESS. POSSIBLE LIVER AND/OR KIDNEY DAMAGE MAY RESULT FROM INGESTION OF LARGE QUANTITIES OF MATERIAL.

PROLONGED OR REPEATED CONTACT MAY CAUSE EYE IRRITATION.

VAPORS AND FUMES MAY BE IRRITATING TO UPPER RESPIRATORY TRACT.

SWALLOWING CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

CHRONIC:

2-ETHOXYETHYL ACETATE IS REPORTED TO CAUSE THE FOLLOWING AFTER REPEATED EXPOSURE:

- TESTICULAR CHANGES, BLOOD CHANGES, BIRTH DEFECTS FETOTOXICITY/EMBRYOTOXICITY, KIDNEY AND LIVER DAMAGE.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

REFER TO PROTECTIVE MEASURES LISTED IN SECTIONS IV., V., VI., VIII. AND IX.
REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE
WITH INERT ABSORBENT.

WASTE DISPOSAL METHOD:

INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE OF
IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL POLLUTION CONTROL REQUIREMENTS.

SECTION VIII - SAFE HANDLING & USE INFORMATION

RESPIRATORY PROTECTION:

ADEQUATE VENTILATION IS REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR DEVICE.
SEE YOUR SAFETY EQUIPMENT SUPPLIER FOR EVALUATION AND RECOMMENDATION.
IN CONFINED AREAS USE NIOSH/MSHA APPROVED AIRLINE RESPIRATOR OR HOOD.

VENTILATION:

PROVIDE SUFFICIENT VENTILATION TO KEEP VAPOR CONCENTRATION BELOW GIVEN TLV AND
LEL. FOR BAKING FINISHES, EXHAUST VAPORS EMITTED ON HEATING. REMOVE
DECOMPOSITION PRODUCTS FORMED DURING WELDING OR FLAME CUTTING OF SURFACES COATED
WITH THIS PRODUCT.

PROTECTIVE GLOVES:

REQUIRED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION:

USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:

EYE BATH AND SHOWER SHOULD BE AVAILABLE. USE CHEMICAL RESISTANT APRON, BOOTS OR
OTHER CLOTHING IF NEEDED TO AVOID REPEATED OR FREQUENT SKIN CONTACT. LIQUID MAY
PENETRATE SHOES AND LEATHER CAUSING DELAYED IRRITATION.

HYGIENIC PRACTICES:

WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. CLOSE CONTAINERS AFTER EACH USE.
CONSULT NFPA CODE FOR ADDITIONAL STORAGE REQUIREMENTS.

OTHER PRECAUTIONS:

DO NOT TAKE INTERNALLY. USE APPROVED BONDING AND GROUNDING PROCEDURES. OBSERVE
LABEL PRECAUTIONS.

APPROVED BY RAW MATERIAL & FORMULA INFORMATION DEPARTMENT

NAME: 

DATE: 9/01/87

FORMULA DATE 11/06/86

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, EXPRESSED OR IMPLIED, EXCEPT THAT IT IS ACCURATE
TO THE BEST KNOWLEDGE OF AKZO COATINGS AMERICA. THE DATA ON THIS SHEET RELIES ONLY TO THE
SPECIFIC MATERIAL DESIGNATED HEREIN. AKZO COATINGS AMERICA ASSUMES NO LEGAL RESPONSIBILITY FOR
USE OR RELIANCE UPON THIS DATA.